



ITEM NO.	W1 Ref.		W2 Ref.		L1 Ref.		L2 Ref.		W ± .015		T Ref.		T1 Ref.	
	Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm	Inches	mm
03-40-108A	.28	7	.16	4	.19	4.8	.05	1.3	.37	9.5	.08	2	.06	1.6
03-40-208A	.28	7	.24	6	.19	4.8	.13	3.3	.37	9.5	.08	2	.06	1.6
03-40-308A	.35	9	.29	7.3	.26	6.6	.12	3	.50	12.7	.16	4	.08	2
03-40-408A	.43	10.8	.36	9.2	.32	8	.19	4.8	.50	12.7	.16	4	.08	2
03-40-508A	.47	11.9	.44	11.2	.36	9.1	.23	5.8	.50	12.7	.16	4	.08	2
03-40-608A	.47	11.9	.51	13	.36	9.2	.33	8.4	.50	12.7	.16	4	.08	2

DOUBLE ADHESIVE TAPE

ADHESIVE	RUBBER
CARRIER	POLYETHYLENE FOAM
THICKNESS	.040 (1mm)
COLOR	WHITE
UL FILE NO.	NA
RoHS COMPLIANCE	YES
SERVICE TEMPERATURE	14 to 113°F (-10 to 45°C)
MR NUMBER	59

MATERIAL	NYLON 66
UL RATING	94V-2
UL FILE NO.	E41938
COLOR	NATURAL
RoHS COMPLIANCE	YES
TEMPERATURE RANGE (REF.)	-40 to 185°F (-40 to 85°C)
MR NUMBER	12

Note: Acrylic adhesive available on request

Nylon 66 rated UL94V-0 available on request  
To order add suffix "X" to item number.

				BY	DATE	Title	
						<b>WIRE ROUTING CLIP</b>	
						Part No.	Issue
						See Table	
<b>C</b>	Changed tape to MR-59	09-18-20	FL	DIMENSIONS		Inches mm	Tolerance .xx = ± .010 .xxx = .005
<b>B</b>	Added " UL94V-0 note	11-10-16	FL	ALL ELECTRONICS HARDWARE		Drwg. type	. CATALOG
<b>A</b>	Corrected value of W1Ref. for item No 03-40-608A	4-20-10	FL	INC.		File No.	03-40series
<b>No</b>	Revision	Date	Init.	2642 Corporate Parkway			
				Algonquin, IL 60102			
				1-800-778-7234			