
06-12 series



	Mounting H	lole Dia.	Holding thickness Range		L		D Dia.		Т		T1	
ITEM NO	Inches	mm	Inches	mm	ln.	mm	ln.	mm	ln.	mm	ln.	mm
06-12-30 06-12-40	.250276 .315325	6.4 - 7 8-8.3	.098315 .118315	2.5 - 8 3 - 8	.897 .830	22.8 21.1	.587 .587	14.9 14.9	.079 .106	2 2.7	.110 .091	2.8 2.3

Packaging 1000 pcs. per bag

NYLON 66, UV STABLE UL94-HB E41938

MATERIAL UL RATING UL FILE NO. BLACK COLOR RoHS COMPLIANCE YES

-40 to 185°F (-40 to 85°C) TEMPERATURE RANGE (REF.)

MR NUMBER

					BY	DATE	Title			
				CUSTOMER APPROVAL			SNAP .RIVETS, TOUGH			
				VERIFIED						
				REVIEWED			Part No.	Issue		
				DRAWN	FL	.8-24-16	.See Table	_		
				DIMENSIONS Inches mm Tolerance .x: ALL ELECTRONICS HARDWARE INC.			x = ± .010 .xxx = .005	7 O I		
							Drwg. type	8-24-16		
				2642 Corpo		CATALOG	0-24-10			
No	Revision	Date	Init.	Algonquin, IL. 6010		File No. 06-12series	♦ □			