



For use where frequent and quick insertions and extractions are required.  
 Average recommended number of applications 25.  
 Color :Black  
 White on special order only. To order add suffix W to item number  
 Packaging : 1000 Pcs / Bag

MATERIAL	NYLON 6
UL RATING	94V-2
UL FILE NO.	E41871
COLOR	BLACK
RoHS COMPLIANCE	YES
TEMPERATURE RANGE (REF.)	-40 to 185°F (-40 to 85°)
MR NUMBER	31

V-0 RATED MATERIAL AVAILABLE ON REQUEST.  
 TO ORDER ADD SUFFIX "X" TO ITEM NUMBER

ITEM NO.	HOLE DIA.		PANEL THICKNESS		L1 Inches ( mm )	L2 Inches ( mm )	W1 Inches ( mm )	W2 Inches ( mm )
	In	mm	Inches	mm				
06-01-3035T	.122 - .126 3.1 - 3.2		.039 - .079	1 - 2	.315 ( 8 )	.14 ( 3.5 )	.118 ( 3 )	.394 ( 10 )
06-01-3045T			.079 - .118	2 - 3		.18 ( 4.5 )		
06-01-3055T			.118 - .157	3 - 4		.22 ( 5.6 )		
06-01-3065T			.157 - .197	4 - 5		.26 ( 6.5 )		
06-01-3075T			.197 - .236	5 - 6		.30 ( 7.5 )		
06-01-3080T			.217 - .256	5.5 - 6.5		.32 ( 8 )		
06-01-3535T	.142 - .146 3.6 - 3.7		.039 - .079	1 - 2	.315 ( 8 )	.14 ( 3.5 )	.138 ( 3.5 )	
06-01-3545T			.079 - .118	2 - 3		.18 ( 4.5 )		
06-01-3555T			.118 - .146	3 - 3.6		.22 ( 5.6 )		
06-01-3570T			.150 - .205	3.8 - 5.2		.28 ( 7 )		
06-01-3580T			.209 - .256	5.3 - 6.5		.32 ( 8 )		
06-01-4050T	.161 - .165 4.1 - 4.2		.098 - .138	2.5 - 3.5		.20 ( 5 )	.157 ( 4 )	.472 ( 12 )
06-01-4060T			.138 - .177	3.5 - 4.5		.24 ( 6 )		
06-01-4070T			.177 - .216	4.5 - 5.5		.28 ( 7.2 )		
06-01-4080T			.216 - .256	5.5 - 6.5		.32 ( 8 )		
06-01-4090T			.256 - .295	6.5 - 7.5		.35 ( 9 )		
06-01-4100T			.295 - .335	7.5 - 8.5		.39 ( 10 )		

				ALL ELECTRONICS HARDWARE , INC. 2642 CORPORATE PARKWAY ALGONQUIN, IL. 60102 1-800-778-7234		Title	RIVETS, "T" TYPE	Issue	0
No	Revision	Date	Init.			File No.	0601T RIVETS	Date	02/10/09